

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

Form Approved

OMB No. 1218-0072

HMTS H-2, F-1, R-0



IDENTITY (As Used on Label and List)

ULTRA TEX

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Manufacturer's Name

Rovaltone Co., Inc.

Emergency Telephone Number

918-663-9666

Address (Number, Street, City, State, and ZIP Code)

9504 E 55th St.

Telephone Number for Information

918-622-6677

Tulsa OK 74145

Date Prepared

1/25/99

Signature of Preparer (optional)

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
---	----------	-----------	--------------------------	--------------

CAS 64742-8807 Petroleum Naphtha

100 ppm

Other Limits Recommended

% (optional)

UN 1255 (solution)

CAS 79-01-6 Trichloroethylene.

50 ppm

UN 1710 (solution)

Boiling Point	360°	Specific Gravity (H ₂ O = 1)	.082
Vapor Pressure (mm Hg.)	0.7	Melting Point	52.4
Vapor Density (AIR = 1)	6.5	Evaporation Rate (Butyl Acetate = 1)	200

Solubility in Water

negligible

Appearance and Odor

amber colored liquid, mild neutral non-residual odor

Flash Point (Method Used)	Flammable Limits	LEL	UEL
T.C.C. 141°F		0.9	6.0

Flash Point (Method Used)

T.C.C. 141°F

Flammable Limits

LEL 0.9

UEL 6.0

Extinguishing Media

foam co2

Special Fire Fighting Procedures

water may be effective

Unusual Fire and Explosion Hazards

none

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid	heat, sparks, flame and contact with strong oxidizing agents
	Stable	X		

Incompatibility (Materials to Avoid) oxidizing agents

Hazardous Decomposition or Byproducts carbon monoxide asphyxiants

Hazardous Polymerization	May Occur		Conditions to Avoid	heat, sparks, flame, contact with strong oxidizing agents.
	Will Not Occur	X		

Section VI — Health Hazard Data

Route(s) of Entry: Inhalation? yes Skin? yes Ingestion? yes

Health Hazards (Acute and Chronic) practically non-irritation to eyes,, moderately irritating to skin, inhalation in high concentrations may result in CNS depression. ingestion may result in vomiting and aspiration into lungs

Carcinogenicity: NTP? NA IARC Monographs? NA OSHA Regulated? yes

Signs and Symptoms of Exposure moderate irritation to mucous membranes. Ingestion harmful or fatal, causes diarrhea and pain

Medical Conditions Generally Aggravated by Exposure pre-existing eye and skin disorders may be aggravated by exposure to product.

Emergency and First Aid Procedures SKIN:wash with soap & water.BREATHING:remove to fresh air.EYES:flush thoroughly with water for at least 15 min. SWALLOWING: call physician, pump stomachDO NOT INDUCE VOMITING

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled do not allow spilled materials to get near very strong oxidizers or sources of heat or open flame. Mop up and dispose in government approved manner. Wash with water containing detergent. Absorb with clay or other inert substance.

Waste Disposal Method Incineration according to air pollution regulations.

Precautions to Be Taken in Handling and Storing harmful or fatal if swallowed. Vapor harmful. Combustible contains petroleum distillates.

Other Precautions keep away from heat or open flame. Use with adequate ventilation. Avoid prolonged breathing of vapor or spray mist. Do not swallow.

Section VIII — Control Measures

Respiratory Protection (Specify Type) use adequate ventilation

Ventilation	Local Exhaust	preferable	Special	none
	Mechanical (General)	acceptable	Other	none

Protective Gloves no Eye Protection recommended

Other Protective Clothing or Equipment none

Work Hygienic Practices use explosion proof ventilation, air dry contaminated clothing in well ventilated

area then launder before re using.